


# BLOQ

creative  
carpet tiles




## THE WORKPLACE CONNEXION


### SPECIFICATIONS

<b>TYPE OF MANUFACTURE</b>	Tufted Loop Pile 1/10"
	ISO 2424
<b>PILE FIBER COMPOSITION</b>	100% Polyamide 6
	ISO 2424 Solution Dyed Nylon made by Aquafil
<b>SECONDARY BACKING</b>	Bitback, Modified Bitumen
	ISO 2424 70% Recycled Content
<b>DIMENSION</b>	50 x 50 cm
	EN ISO 24342
<b>PILE WEIGHT</b>	540 g/m <sup>2</sup>
	ISO 8543
<b>SURFACE PILE WEIGHT</b>	330 g/m <sup>2</sup>
	ISO 8543
<b>TOTAL WEIGHT</b>	4 250 g/m <sup>2</sup>
	ISO 8543
<b>TOTAL THICKNESS</b>	6.0 mm
	ISO 1765
<b>PILE HEIGHT</b>	2.7 mm
	ISO 1766
<b>PILE DENSITY</b>	0.123 g/m <sup>3</sup>
	ISO 8543
<b>NUMBER OF TUFTS</b>	156 000 /m <sup>2</sup>
	ISO 1763
<b>DIMENSIONAL STABILITY</b>	≤ 0.2%
	ISO 2551
<b>NUMBER OF COLOURS</b>	8
<b>PACKAGING</b>	Box: 20 tiles / 5 m <sup>2</sup> Pallet: 200 m <sup>2</sup>


### PERFORMANCE

<b>CLASSIFICATION</b>	33
	EN 1307
<b>LUXURY RATING</b>	LC1
	EN 1307
<b>CASTOR CHAIR RATING</b>	A: Intensive use
	EN 985
<b>FIRE CLASSIFICATION</b>	B <sub>fl</sub> -s1
	EN 13501-1
<b>IMPACT SOUND INSULATION</b>	ΔL <sub>w</sub> : 25 dB
	EN ISO 10140-3
<b>SOUND ABSORPTION</b>	Frequency Hz 125 250 500 1000 2000 4000
	EN ISO 354 α <sub>s</sub> 0.00 0.03 0.06 0.16 0.30 0.35
<b>NOISE REDUCTION</b>	α <sub>w</sub> : 0.15
	EN ISO 354
<b>PERMANENT ANTISTATIC</b>	≤ 2 kV
	ISO 6356
<b>TRANSVERSAL RESISTANCE</b>	≤ 1 X 10 <sup>9</sup> Ohm
	ISO 10965
<b>THERMAL RESISTANCE</b>	0.064 m <sup>2</sup> K/W
	ISO 8302
<b>COLOUR FASTNESS TO LIGHT</b>	≥ 7
	EN ISO 105-B02
<b>COLOUR FASTNESS TO WATER</b>	≥ 4
	EN ISO 105-E01
<b>RUBBING FASTNESS</b>	≥ 4
	EN ISO 105-X12
<b>GUT N° PRODIS</b>	0D32FA3E







Made in the Netherlands (EU)



EMISSIONS DANS L'AIR INTERIEUR: A+



AQUAFIL synthetic fibres and polymers



**EN 14041**  
DOP: 1137-127856  
NB: 2401  
20  
**CE**  
Bfl-s1 DS PCP NA HCHO  
λ23 λ23  
For use as floor covering in buildings.  
BLOQ  
De Blokmat 29  
NL - 8281 JH Genemuiden

**BSI 14041**  
DOP: 1137-127856-UK  
AB: 2401  
20  
**UK CA**  
Bfl-s1 NCS PCP  
NA HCHO λ23 λ23  
FOR USE AS FLOOR COVERING IN BUILDINGS.  
BLOQ  
De Blokmat 29  
NL - 8281 JH Genemuiden

All rights reserved to alter technical specifications.